
Armitron Watch Battery Replacement

Armitron
Watch
Battery
Replacement

Downloaded from
www.strongadvocates.com
by Diaz & Hayden

KEEP YOUR TIMEPIECE TICKING: A COMPLETE GUIDE TO ARMITRON WATCH BATTERY REPLACEMENT

There is something quietly frustrating about glancing at your wrist only to realize your watch has stopped. For owners of Armitron watches—a brand known for blending affordability with reliable quartz movement—this moment usually signals one thing: the battery

has run its course. While it might be tempting to toss the watch in a drawer or assume a costly repair is ahead, **Armitron watch battery replacement** is often a straightforward task that can bring your favorite timepiece back to life in minutes. Whether you own a classic analog model, a rugged sports watch, or a sleek digital chronograph, understanding how to approach this process saves you time, money, and a trip to the jeweler. In this guide, we will walk through

everything you need to know about Armitron watch battery replacement. From recognizing the early signs of a dying battery to selecting the correct replacement cell and performing the swap yourself, this article covers it all. We will also discuss when it is wiser to seek professional help, how to avoid common mistakes, and practical tips to maximize battery life so you can enjoy your Armitron for years to come.

RECOGNIZING THE SIGNS: WHEN DOES YOUR ARMITRON NEED A NEW BATTERY?

Before diving into the replacement process, it helps to know what to look for. Modern quartz watches, including most Armitron models,

give subtle warnings before the battery finally gives out. Recognizing these early indicators can prevent sudden stoppages and protect the movement from potential damage caused by a leaking battery.

The Second Hand Becomes Erratic

One of the most common signs is a second hand that begins to jump in multi-second increments. For example, the hand might tick four or five seconds at a time

instead of a smooth one-second sweep. This is often a low-battery indicator designed into the quartz movement, and it means the watch is conserving power. When you see this behavior, the battery typically has only a few days or weeks of life left.

Diminished Brightness on Digital Displays

If your Armitron is a digital model, a fading or dim display is a clear signal. The

numbers may appear faint, flicker, or become hard to read in normal light. This happens because the voltage from the battery drops below the threshold needed to power the LCD screen properly.

The Watch Stops Completely

Of course, the most obvious sign is a watch that no longer runs. In many cases, the watch stopped due to a depleted battery. Before assuming the movement has failed, a simple battery replacement is the first

and most likely solution.

Inconsistent Timekeeping

If your Armitron starts losing or gaining several minutes each day, the battery could be struggling to provide stable power to the quartz crystal oscillator. While this can sometimes indicate a deeper issue, a fresh battery is the easiest fix to try first.

ESSENTIAL TOOLS FOR ARMITRON WATCH BATTERY REPLACEMENT

Performing an Armitron watch battery

replacement at home requires a few specific tools. While it is possible to improvise, using the correct equipment reduces the risk of scratching the case, damaging the movement, or losing tiny components. Here is what you will need:

- **Case back opener:** Depending on your watch model, you may need a screw-type opener, a wrench for hexagonal backs, or a thin blade for snap-off backs.
- **Small precision screwdriver set:** Useful for prying open snap-on backs and handling battery clamps.
- **Non-metallic tweezers:** Metal

tweezers can short-circuit the battery or scratch delicate parts. Plastic or nylon tweezers are safer.

- **A new battery of the correct type:** Common Armitron batteries include SR626SW, SR920SW, SR927SW, and CR2016 for some digital models. Check the old battery or your manual.
- **A soft cloth or watch mat:** Prevents scratches on the crystal and case during handling.
- **Magnifying glass or loupe:** Helps when reading tiny markings on the battery or

inspecting the movement.

STEP-BY-STEP ARMITRON WATCH BATTERY REPLACEMENT GUIDE

Now that you have the tools and a fresh battery, let us go through the process step by step. Keep in mind that Armitron watches vary in design, so some details may differ slightly between models. However, the general procedure remains consistent.

Step 1: Identify Your

Case Back Type

Step 2: Open the Case Back

Turn your Armitron over and examine the case back. There are three common types: a snap-off back, a screw-down back with notches, or a screw-down back with a hexagonal shape. Knowing which type you have determines the tool you need. Snap-off backs are common on budget-friendly Armitron models, while screw-down backs are more typical on water-resistant sports watches.

For a **snap-off back**, locate a small groove or notch along the edge. Insert a thin blade or a case back knife into the groove and gently pry upward. Work your way around the edge until the back pops loose. Apply steady, even pressure to avoid bending the case back.

For a **screw-down back with notches**, use a case back opener tool with adjustable pins. Fit the pins into the notches, turn counterclockwise, and unscrew the back. For **hexagonal backs**, a

wrench or adjustable spanner works best.

Step 3: Remove the Old Battery

Once the case back is off, you will see the movement and the battery held in place by a small metal clamp or a plastic retainer. Use your non-metallic tweezers to gently release the clamp or lift the old battery out. Take note of the battery's orientation—the positive side is usually marked with a plus sign and typically faces up, but this can vary by movement.

Important: Avoid touching the battery

with bare fingers. Oils from your skin can affect the electrical contact and shorten the life of the new battery.

Step 4: Insert the New Battery

Using your tweezers, pick up the new battery by its edges and place it into the compartment in the same orientation as the old one. Press it down gently until the clamp or retainer snaps back into place. Ensure the battery sits flat and makes solid contact with the metal terminals.

Step 5: Check the Watch Function

Before sealing the watch, test that it is running. If your Armitron has a quartz analog movement, the second hand should begin moving immediately. For digital models, the display should light up or show the time. If nothing happens, double-check the battery orientation and ensure the contacts are clean and making proper contact.

Step 6: Replace the Case Back

Line up the case back with the watch body. For snap-off backs, press firmly around the perimeter until it clicks into place. For screw-down backs, turn clockwise until snug. Be careful not to overtighten, as this can damage the threads or squeeze the gasket out of alignment.

Step 7: Verify

Water Resistanc e

If your Armitron is water-resistant, the case back gasket helps keep moisture out. After replacing the back, it is wise to have the water resistance tested by a professional if you intend to swim or shower with the watch. For most daily wear, a careful hand-tightening is sufficient for splashes and rain.

SELECTING THE RIGHT BATTERY FOR YOUR ARMITRON WATCH

Choosing the correct battery is critical for reliable performance. Armitron uses several

common battery sizes, and using the wrong type can lead to poor contact, shortened life, or even damage to the movement. Here are the most common batteries found in Armitron watches:

- **SR626SW (also known as 377):**
A silver oxide battery commonly used in many analog dress watches from Armitron.
- **SR920SW (also known as 371):**
Often found in larger analog watches with chronograph subdials.
- **SR927SW (also known as 395):**
Used in mid-size analog models and some digital-analog combos.
- **CR2016 or CR2025:** Lithium

PROFESSIONAL

replaced in many digital Armitron watches, especially those with backlight features.

- **SR621SW (also known as 364):** Common in smaller or women's Armitron watches.

The easiest way to confirm the correct battery is to remove the old one and read the number printed on its surface. If the number is worn off, consult the watch manual or search online using your specific model number, which is usually engraved on the case back.

DIY VS.

REPLACEMENT: WHICH IS RIGHT FOR YOU?

Armitron watch battery replacement can certainly be done at home, especially if you are comfortable working with small components. However, there are situations where professional service is the better choice.

When DIY Makes Sense

- You own a basic analog or digital Armitron with a snap-off back.
- You have the proper tools and a steady hand.
- You are replacing

the battery as routine maintenance and the watch has no other issues.

- You are willing to accept the risk of minor scratches or a lost gasket.

requires specialized tools.

- You notice corrosion, rust, or leaking around the old battery.
- You need the water resistance tested and certified after the replacement.
- You simply do not want to risk damaging your watch.

When to Call a Professional

- Your Armitron is a higher-end model with complex complications like a chronograph, alarm, or dual time zone.
- The watch has a screw-down case back that

A professional jeweler or watch repair shop typically charges a modest fee for battery replacement, often including a new gasket and a water resistance check. For many people, this peace of mind is well worth the cost.

COMMON MISTAKES TO AVOID DURING

BATTERY REPLACEMENT

Even a simple battery change can go wrong if you are not careful. Here are the most common pitfalls and how to avoid them:

1. **Using the wrong battery type:** Always match the old battery's number exactly. Silver oxide and alkaline cells of the same size are not interchangeable.
2. **Handling the battery with bare fingers:** Skin oils can cause poor contact and corrosion. Always use tweezers or wear clean gloves.
3. **Forgetting the**

gasket ARMITRON WATCH

watch has a rubber gasket around the case back, make sure it is seated properly before closing. A missing or pinched gasket compromises water resistance.

4. **Overtightening the case back:** This can strip threads or crack the crystal. Snug is sufficient.
5. **Prying too aggressively:** Watch backs are thin and can bend or warp if you apply too much force. Work slowly and carefully.
6. **Ignoring corrosion:** If the old battery has leaked, the movement may

need cleaning by a professional. Simply putting in a new battery may not work and could cause further damage.

EXTENDING THE LIFE OF YOUR NEW ARMITRON WATCH BATTERY

Once you have completed the Armitron watch battery replacement, you naturally want the new battery to last as long as possible. Here are practical tips to maximize battery life:

- **Minimize chronograph and alarm use:** These features consume more power. Use them only when needed.
- **Avoid extreme temperatures:**

Heat accelerates battery drain, and cold can temporarily reduce voltage. Store your watch in a moderate climate.

- **Keep the watch away from strong magnetic fields:** Magnets can interfere with the quartz movement and cause the battery to work harder.
- **Consider a watch winder for automatic models:** This tip applies only if you own an automatic Armitron, but it is worth mentioning for completeness.
- **Remove the battery if**

storing the watch long-term:

If you plan not to wear the watch for months, take the battery out to prevent leakage

and corrosion.

- **Turn off unnecessary features:** On digital models, turn off the hourly chime, backlight